

LED Greentube - T8

Greentube provides high quality light comparable to conventional fluorescent and delivers the immediate benefits of LED lighting technology. With its simple design, it is easy to install in any location.

AC Input: 200 ~ 240Vac
System Power: 18W +/-5%
Color Rendering Index (CRI): >80
Operating Temperature: -20°C ~ +40°C
Storage Temperature: -20°C ~ +80°C
Lifetime (typical): 40,000 hours at ta 25°C
Usage: 12 hours a day
LED Lumen Maintenance: LM80
Electrical Safety: Class II
Compliant: CE
Weight: 250g
Luminaire Material: Frosted Polycarbonate
Size(L) X (Ø) : 1198mm x 26mm



Application areas

- Homes
- Offices
- Car parks
- Covered walkway
- Shopping malls
- Warehouses

Details	Model	RS-PVN-4FT-18W-CW-PC	RS-PV-4FT-18W-CW-PC
Luminous Flux (Hot Lumens)		1,800lm	2,300lm
Luminous Efficacy		>100 lm/W	>120 lm/W
Colour Temperature		6500k (available 3000k, 4000k)	Warm White (2850K - 3250K)
Beam Angle		180°	300°



NexusLED®

Simple is Better

Designed and Manufactured By:

NexusLED Green Technology Sdn. Bhd. (893555-V)

No. 6, Jalan Sri Sulong Selatan, Taman Industri Sri Sulong, 83000 Batu Pahat, Johor,
Malaysia. Tel: +607-4102 159 Fax:+607-4102 206

For inquiry please contact us at: info@nexusled.com

© 2019 NexusLED Green Technology Sdn. Bhd. All rights reserved. NexusLED does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by NexusLED. All trademarks are owned by NexusLED Green Technology Sdn. Bhd. or their respective owners.

Revision 022005



For More Information
Please Scan The QRCode
Or visit www.nexusled.com