

NexusLED®
Simple is Better

Indoor Illumination PANEL LIGHT

NexusLED LED Panel Lights offer sleek design and uniform, glare-free illumination, ideal for offices, retail spaces, and more. Energy-efficient and durable, they're perfect for creating bright, comfortable environments.

LED Panel Light Back-lit Series

Nexusled Back-lit panel series are designed engineered to fit recessed ceiling systems with grid size ranging from 595x595mm up to 595x1195mm. These Back-lit panels are fitted with easy-access external drivers for extended flexibility. Color temperatures (Cool, Neutral, Warm) are available upon request.



Application areas

- Elevators
- Conference Rooms
- Foyers
- Garages
- Offices
- Bathrooms
- Corridors

Product Specifications

AC Input: 220-240V

ICompliant: IEC, Sirim

Color Rendering Index (CRI): >80

Housing material: Metal With Powder Coating

Beam angle: 120°

Lifetime (typical): 50,000 hours at ta 25°C

LED Driver: Non flicker-free (Option- flicker-free)

Luminaire Cover Material: PS

Color Temperature: 3000K - 6500K

IK Rating: IK02


LED Lumen Maintenance: LM80

IP Rating: IP20

Electrical Safety: Class

Model	603mm x 1208mm 295mm x 1195mm	603mm x 603mm 595mm x 595mm	603mm x 1208mm 595mm x 1195mm
System Power	36W ± 4W	36W ± 4W	60W ± 4W
Luminous Flux	4,490 lm	4,620 lm	7,000 lm
Luminaire Efficacy	>120 lm/W	>120 lm/W	>120 lm/W
LED Driving Current	1000 mA	1000 mA	1500 mA
LED Quantity	48pcs	60pcs	120pcs

Dimensions




Thincredible



Weighing only 1.0kg~2.0kg per unit and only ~41mm thick!


Photometry



303mm x 1208mm
295mm x 1195mm

603mm x 603mm
595mm x 595mm

603mm x 1208mm
595mm x 1195mm




Metric	L	W	H	Cut-out	Weight
1' x 4'	295mm	1195mm	41mm	285mm x 1185mm	± 1.2kg
2' x 2'	595mm	595mm	41mm	585mm x 585mm	± 1.0kg
2' x 4'	595mm	1195mm	41mm	585mm x 1185mm	± 2.0kg

Imperial	L	W	H	Cut-out	Weight
1' x 4'	303mm	1208mm	35mm	283mm x 1193mm	± 1.0kg
2' x 2'	603mm	603mm	35mm	583mm x 583mm	± 1.0kg
2' x 4'	603mm	1208mm	35mm	583mm x 1193mm	± 2.0kg


Panel Light Accessories (Optional)




Application Direction



Recessed



Surface



Pendant



Designed and Manufactured By:

NexusLED Green Technology Sdn. Bhd. (893555-V)

No. 32-40, Jalan Sri Sulong Selatan, Taman Perindustrian Sri Sulong, 83000 Batu Pahat, Johor,

Malaysia Tel: +607-4102 159 Fax: +607-4102 206

For inquiry please contact us at: info@nexusled.com

© 2023 NexusLED Green Technology Sdn. Bhd. All rights reserved. NexusLED does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by NexusLED. All trademarks are owned by NexusLED Green Technology Sdn. Bhd. or their respective owners.

Revision 250123



For More Information
Please Scan The QR Code
Or visit www.nexusled.com